



- NOTE:
- USE 4043 WELD WIRE.
 - 6063 ASSEMBLY .375 WALL OR LESS TO BE HEAT-TREATED TO T6 TEMPER AFTER WELDING.
 - POLE ASSEMBLY TO BE SUPPLIED WITH 1 1/4" I.D. RUBBER GROMMET FOR WIRING TO TRAFFIC MAST ARM (FIELD DRILL 1 1/2" DIA. HOLE).

ALL.	DESCRIPTION	DATE	BY	CHK	MATERIAL	P&K	
A	WAS 15" BOLT CIRCLE	07-15-94	W/V			P&K POLE PRODUCTS, INC. 84 Foundry St., Newark, N.J.	
B1	WAS 6'-0" TOP STR.				STEEL SIZE	TITLE	
B2	WAS AL. ALLOY DOOR					S1080019063K-70	
B3	DELETED GRD. CLIP	08-04-94	W/V		FINISH OR REPER	BERGEN CODE ST10-1906	
C	WAS 5'-0" TOP STR.	08-21-95	W/V			DR. H.M.S.	03-31-92
D	DELETED WIRE HOLE	12-09-97	W/V			DR. W.W.V.	03-31-92
CUSTOMER						SCALE	REV. NO.
BERGEN COUNTY DEPT. OF PUBLIC WORKS						NONE	C-100901