WW200

Wrong-Way Vehicle Detection and Warning System Data Sheet

* carmanah®



- Configurable radar settings for detection speed and sensitivity
- Highest LED intensity output in the industry
- ✓ Mounts to standard poles
- Scalable design: multiple signs can be added with synchronized flashing
- Customizable settings and sign sizes
- Powered by solar or AC
- ✓ Solar Power Report[™] (SPR) prepared for every location to ensure battery longevity

Wrong-way vehicle detection systems are up to 80% effective in stopping wrong-way drivers*.



The system monitors highway ramps 24 hours a day for wrong-way vehicles without interfering with other traffic detection systems. When the radar unit detects a wrong-way vehicle, the system activates the LEDs to warn the driver of their error and encourage self-correction.

Easy Solar Installation

With its highly efficient and compact design, installation is quick and uncomplicated, dramatically reducing installation costs. Existing WRONG WAY signs can be retrofitted in minutes, and new installations can be completed without the cost of larger poles, new bases and trenching.

Advanced User Interface

The WW200 comes with an on-board user interface for quick LED configuration and system status monitoring. It allows for simple, in-the-field adjustment of flash pattern, duration, intensity, ambient auto adjust, night dimming, and more. The radar is easily programmed using the included PC software, allowing for quick setting configuration for detection speed, sensitivity and more.

Reliable

Carmanah backs every system with a three-year limited warranty. Every solar-powered model is solar-sized by location to ensure year-after-year operation. Carmanah includes a Solar Power Report to prove sustainability over a 12-month period.





MUTCD compliant



3-year limited warranty



Buy America compliant



Solar-sized for every location

Nevada DOT, Wrong Way Driver System, preliminary research press release.

WW200

Wrong-Way Vehicle Detection and Warning System Data Sheet

1.844.412.8395 | traffic@carmanah.com | carmanah.com

SOLAR ENGINES







Large, 30w integrated solar engine



Cabinet-based, 20w, 50w, and 80w solar and AC systems

R5-1a



LED ENHANCED WRONG WAY SIGN

36" x 24" (914 mm x 610 mm)



carmanah®

42" x 30" (1067 mm x 762 mm)

MUTCD	Chapter	2B	compliant,	R5-	1a layout

3M Diamond Grade DG3 retroreflective sheeting, 4092 red

8 red LEDs

36" and 42" sign sizes

SOLAR ENGINE MOUNTING

2.0"- 2.5" Perforated Square Pole Mount



2.38" - 2.88" Diameter Round Pole Mount




3.5" - 4.5" Diameter

Side Pole Mount



LED SIGN MOUNTING


Through Bolt



U Bolt



Banding to Pole



SYSTEM SPECIFICATIONS

Warranty

SYSTEM SPECI	FICATIONS				
On-Board User Interface	Adjustable system settings with auto-scrolling LED display				
	System test, status, and fault detection: battery, solar, beacon, day/night				
	Intensity setting: 20 to 1400 mA for LED enhanced signs				
	Radio settings: enable/disable, selectable channel from 1 to 14				
	Nighttime dimming: 10 to 100% of daytime intensity				
	Ambient Auto Adjust: increases intensity during bright daytime				
	Automatic Light Control: reduces intensity if the battery is extremely low				
Connectivity	Encrypted, wireless radio with 2.4 GHz mesh technology				
	User-selectable multiple channels to group different signs and ensure a robust wireless signal				
	Communicates with all nearby WW200 and WW100 wrong-way warning systems				
	Instantaneous wireless activation: <150 ms				
	Wireless range: 1000 ft (305 m)				
	Integrated, vandal-proof antenna				
	Solar or AC-powered				
Energy Collection	45-degree solar panel tilt for optimal energy collection				
	Maximum Power Point Tracking with Temperature Compensation (MPPT-TC) battery charger for optimal energy collection in all solar and battery conditions				
	Replaceable, recyclable, sealed, maintenance-free, best-in-class AGM batteries offer the widest temperature range and longest life				
Energy Storage	Battery design life: +5 yrs.				
	Tool-less battery change with quick connect terminals and strapping for easy installation				
Solar Engine Construction	Weatherproof, gasketed enclosure with vents for ambient air transfer (NEMA 3R)				
	Lockable, hinged enclosure for access to on-board user interface and batteries				
	Corrosion-resistant aluminum with stainless steel hardware				
	Raw aluminum finish or powder coated in yellow or black				
	Prewired to minimize installation time				
	High-efficiency optics and EMS = the most compact, lightweight system				
Environmental	-40 to 165° F (-40 to 74° C) system operating temperature				
	-40 to 140° F (-40 to 60° C) battery operating temperature				

3-year limited warranty (1-year battery warranty)

DETECTOR SPECIFICATIONS

24 GHz radar unit detects wrong-way vehicle

Radar technology for accurate detection at night and in adverse weather conditions

Radar Unit

Adjustable radar parameters, such as detection speed, sensitivity, trigger event settings and duration, and others

3rd-party tested radar detection range to $\underline{1}000 \text{ ft}$

Universal bracket mounts to pole with standard banding, through bolts, U-bolts, band clamps, and more

WARNING LIGHT SPECIFICATIONS

LED Enhanced Sign MUTCD compliant: 2009 MUTCD, Chapter 2B Signs

High-power LEDs in waterproof housings

Aluminum channels protect wiring; includes junction box

 $\label{lem:specifications} \textbf{Specifications subject to local environmental conditions, and may be subject to change.}$

All Carmanah products are manufactured in facilities that are certified to ISO quality standards.

"Carmanah" and Carmanah logo are trademarks of Carmanah Technologies Corp.

© 2022, Carmanah Technologies Corp.

Document: Carmanah_DATA_WW200_RevB