

10/100 Mbps Ethernet 8 port unmanaged switch
4 Ports: Electrical ↔ 4 Ports: SFP Optical
8 Ports: Electrical
8 Ports: SFP Optical



Description

The ComNet™ CNFE8US Series Ethernet 8 port unmanaged switch is designed to transmit and receive 10/100 Mbps data over optical fiber through user selectable SFP options or 10/100 Mbps data over CAT5E/6 electrical cable. This unit integrates eight independent 10/100 Mbps channels in a single package. The CNFE8FX4TX4US and CNFE8FX8US require the ordering of sold-separately interchangeable SFP modules for fiber type, distance and connectors. All electrical interfaces will Auto-Negotiate to 10 Mbps, or 100 Mbps Ethernet rate without any adjustments. The optical interfaces operate at a 100 Mbps Ethernet rate. The CNFE8US Series models are environmentally hardened to operate in demanding environments. LED indicators are provided for confirming equipment operating status. Packaged in the exclusive ComNet ComFit housing, these units may be either wall or rack-mounted, or may be DIN-rail mounted by the addition of ComNet model DINBKT1 adaptor plate.

Applications

- 10/100 Mbps Ethernet
- High Speed Computer Links

Features

- 10/100 Mbps Ethernet
 - 10/100 BASE-T/TX electrical port
 - 100 BASE-FX optical port
- Electrical ports support Auto-Negotiation for 10 Mbps or 100 Mbps, full duplex or half duplex data.
- Optical port supports 100 Mbps full duplex data
- Automatic MDI/MDI-X crossover
- Designed to meet full compliance with the environmental requirements (ambient operating temperature, mechanical shock, vibration, humidity with condensation, high-line/low-line voltage conditions and transient voltage protection) of NEMA TS-1/TS-2 and the Caltrans Specification for Traffic Signal Control Equipment.
- Uses interchangeable SFP for fiber type, distance and connector (Ordered separately)
- Voltage transient protection on all power and signal input/output lines provides unconditional protection from power surges and other voltage transient events.
- No in-field optical adjustments required
- Power, Activity and Port status LED indicators
- Hot-swappable rack modules
- Interchangeable between stand-alone or rack mount use - ComFit
- IEEE 802.3 compliant
- Lifetime Warranty

(SFP) = Small Form-Factor Pluggable Module



CNFE8US Series

specifications

DATA

Data Interface:	Ethernet
Data Rate:	10/100 Mbps IEEE 802.3 Compliant Full Duplex or Half Duplex Electrical Ports/Full Duplex Optical Port

FIBERS*

SFP Dependent

CABLE

CAT5E/6

FIBER CONNECTORS

Requires selection of sold-separately SFP modules. See ComNet data sheet for number and description of SFP modules

CONNECTORS

Power:	Terminal Block
Data:	RJ45

LED INDICATORS

- Optical Link/Data Activity
- Electrical Link/Data Activity
- Power

ELECTRICAL & MECHANICAL

Power:	12-24 VDC @ 700 mA
Surface Mount:	From Rack
Rack Mount:	
Number of Rack Slots:	2
Current Protection:	Automatic Resettable Solid-State Current Limiters Meets IPC Standard
Circuit Board:	
Size (in./cm) (L×W×H)	6.1 × 5.3 × 2.2 in., (15.5 × 13.5 × 5.6 cm)
Shipping Weight:	<2 lbs./0.9 kg

ENVIRONMENTAL

MTBF:	>100,000 hours
Operating Temp:	-40° C to +75° C
Storage Temp:	-40° C to +85° C
Relative Humidity:	0% to 95% (non-condensing) [†]

* Multimode fiber needs to meet or exceed fiber standard ITU-T G.651.
 Single mode fiber needs to meet or exceed fiber standard ITU-T G.652.

[†] May be extended to condensation conditions



PART NUMBER	DESCRIPTION	DISTANCE
CNFE8FX4TX4US	8 Port 10/100 Mbps Ethernet Unmanaged Switch; 4 TX, 4 FX	See SFP Modules data sheet for optional distances, fiber type and connector type.
CNFE8FX8US	8 Port 100 Mbps Ethernet Unmanaged Switch; 8 FX	
CNFE8TX8US	8 Port 10/100 Mbps Ethernet Unmanaged Switch; 8 TX	100 m (330 feet)
Accessories	12 Volt DC Plug-in Power Supply, 90-264 VAC, 50/60 Hz (Included)	
Options	Add suffix '/C' for Conformally Coated Circuit Boards (Extra charge, consult factory) Small Form-Factor Pluggable Modules (See SFP Data sheet) DIN-Rail Mounting Adaptor Plate Kit – With mounting hardware (Optional, order model DINBKT1)	

NOTE: This product requires a fiber installation with a minimum 30 dB connector return loss.

The use of Super Polish Connectors is recommended.

Complies with FDA Performance Standard for Laser Products, Title 21, Code of Federal Regulations, Subchapter J

In a continuing effort to improve and advance technology, product specifications are subject to change without notice.



3 CORPORATE DRIVE | DANBURY, CT 06810 | USA
 T: 203.796.5300 | F: 203.796.5303 | TECH SUPPORT: 1.888.678.9427 | INFO@COMNET.NET
 8 TURNBERRY PARK ROAD | GILDERSOME | MORLEY | LEEDS, UK LS27 7LE
 T: +44 (0)113 307 6400 | F: +44 (0)113 253 7462 | INFO-EUROPE@COMNET.NET