



DBL Series LED UPS

Specifications:

Rating

- DBL 700 - 700 W
- DBL 1400 - 1400 W
- DBL 2100 - 2100 W

Input

- DBL 700/1400/2100 - 120VAC

Output

- DBL 700/1400/2100 - 120VAC

Regulation

- DBL 700/1400/2100 - +/- 2%

Frequency

- DBL 700/1400/2100 - 50/60Hz

Output Wave Form

- DBL 700/1400/2100 - Sine wave

Harmonic Distortion

- DBL 700/1400/2100 - Less than 5%

Power Factor

- DBL 700/1400/2100 - 1

Topology

- DBL 700/1400/2100 - Double conversion

LED Indicators

- DBL 700/1400/2100 - Load, battery charge, line, low battery, fault, overload, and bypass

Transfer to Battery

- DBL 700/1400/2100 - 0 ms

Protection

- DBL 700/1400/2100 - Electronic circuit and fuse

Relay Outputs

- DBL 700/1400/2100 - UPS fail, AC fail, on battery, and low battery

Overload

- DBL 700/1400/2100 - 125% for 10 minutes then the UPS goes to bypass

Features

- Double-conversion, true on-line design
- Operates in temperatures of up to 165.2°F (74°C)
- 700, 1400, and 2100 W ratings
- Continuous voltage regulation
- Output isolation
- Complete power conditioning
- High rate 200 W charger for fast recharge time
- Self-diagnostics and battery testing
- 19-inch rack-mount design for easy maintenance
- Anderson Power Pole DC connector
- Excellent voltage regulation +/- 3%
- RS 232 port with monitoring software
- Screw terminal relay output
- Replaceable surge suppressor
- Reset-able battery run time meter
- Power failure event counter

Options:

- 24/7 time with logging
- Flash 10-hour timer
- Hot Swap fail-safe bypass
- Extended run time 10 hours or longer
- 400W charger
- Rack mounting ears

Protection:

Spike Suppression

- IEEE 587 A & B

Lightning

- 8/20U sec 5000A

EMI/RFI

- GB9254

Attenuation

- < 45DB @ 1 MHz for normal/common mode

Battery System:

Battery Bank

- 36VDC

Battery Charger

- 200W @ 36VDC

Battery Connection

- Anderson Power Pole

Recharge Time

- Less than 8 hours

Battery Protection

- Dual segment before shut down

Mechanical:

Weight

- DBL 700 - 18lb
- DBL 1400 - 23lb
- DBL 2100 - 30lb

Environmental:

Temperature Operation

- -22°F to 165.2°F (-30°C to + 74°C)

Humidity

- 10% to 90% non-condensing

© 2011 Econolite Control Products, Inc. All rights reserved. Econolite Control Products, Inc. reserves the right to change or update these specifications at any time without prior notification

3360 E. La Palma, Anaheim, CA 92806-2856
Tel: (714) 630-3700 • Fax: (714) 630-6349
E-mail: sales@econolite.com
38404E0607-6



 **ECONOLITE**[®]
An Econolite Group Company