

PS 200

What, exactly, is a PS 200?

Econolite's PS Series of power supply units supplies regulated DC power, and unregulated AC power, and a line frequency reference for the detector rack, BIUs, load switches, and other auxiliary equipment. The PS Series meets all requirements and NEMA standards. All TS-2 Type 1 cabinets and TS-2 Type 2 cabinets that utilize a BIU require a PS unit.

About the PS-200

The PS-200 cabinet power supply is a shelfmounted unit, which supplies regulated DC power, unregulated AC power, and a line frequency reference for the detector rack, BIUs, load switches, and other auxiliary equipment. The PS-200 meets all requirements of the NEMA TS2-2003 standard. All TS-2 Type 1 cabinet assemblies require the use of this unit, as well as any TS-2 Type 2 cabinet assemblies that utilize Bus Interface Units (BIU). Each PS-200 cabinet power supply is put through a rigorous quality program and tested under the extreme environmental conditions experienced on the street.



Display Indicators

A separate LED indicator is provided to display output status and fuse integrity for the three supply outputs. The Line Frequency Reference LED indicator pulses to show 60 Hz activity.

Input / Output Pins

- A AC Neutral
- B Line Frequency Reference Output
- C AC Line Input
- D +12 VDC Output
- E +24 VDC Output
- F Reserved
- G Logic Ground
- H Earth Ground
- I 12 VAC Output
- J Reserved

Output Protection

The +12 VDC, +24VDC, and 12 VAC outputs are fused for over-current protection. Each output is protected against voltage transients by a 1500 Watt suppressor.

Test Points

Individual test jacks are provided for the +12 VDC output, +24 VDC output, and Logic Ground reference.

Basic Specifications

- Dimensions
 - 6" H x 5.8" W x 8.3" D

