


# Opticom<sup>™</sup> Infrared System Opticom<sup>™</sup> 700 Series Phase Selectors Accessories

# **Opticom™ Infrared System Matched Component Products**

October 2007



Opticom™ Model 758 Auxiliary Interface Panel

# Opticom<sup>™</sup> Model 758 Auxiliary Interface Panel

## **Description**

Opticom<sup>™</sup> Model 758 Auxiliary Interface Panel (AIP) provides a convenient area to interconnect Opticom<sup>™</sup> Phase Selectors or Opticom<sup>™</sup> Discriminators with terminals inside a traffic cabinet.

The Opticom model 758 contains two terminal blocks for wiring to the traffic cabinet signals and a 44-pin D-subminiature connector for the auxiliary interface cable.

#### **Features**

- Conveniently located connections and harnessing
- Rugged construction
- Convenient interconnections to cabinet wiring
- Compatibility with 22 to 16 AWG wires
- Easy-to-read terminal designations
- Easy installation

#### **Physical Dimensions**

**Length:** 7.25 in. (18.4 cm) **Width:** 4.5 in. (11.4 cm) **Height:** 1.25 in. (3.2 cm) **Weight:** 0.5 lbs. (230 g)



Opticom™ Model 832 Communications Daughter Board

# Opticom™ Model 832 Communications Daughter Board

### **Description**

Opticom™ Model 832 Communications
Daughter Board is an optional plug-in module
for Opticom™ 700 Series Phase Selectors.
It is designed to provide additional
communications features. The Opticom model
832 allows the user to independently set
communications data rates for the front and
rear serial communications ports. It also
provides additional drive capability and
termination resistor options to put several
Opticom 700 series phase selectors on the same
communications line.

#### **Features**

- Plugs directly into Opticom<sup>™</sup> Models 754, 754N, 752 and 752N Phase Selectors
- Contains jumper-selected termination and pull-up options
- Has independent front panel and rear backplane communications rates

### **Physical Dimensions**

**Length:** 2.0 in. (5.1 cm) **Width:** 0.75 in. (1.9 cm) **Height:** 0.75 in. (1.9 cm) **Weight:** 0.35 lbs. (10 g)



Opticom™ Model 755 Four-Channel Adapter Card

# Opticom™ Model 755 Four-Channel Adapter Card

# **Description**

The Opticom<sup>™</sup> Model 755 Four-Channel Adapter Card supports Opticom<sup>™</sup> Models 754, 454 and 254 Phase Selectors in an Opticom<sup>™</sup> Model 560 Card Rack and in NEMA card racks that are wired for two-channel Opticom<sup>™</sup> Phase Selectors and Opticom<sup>™</sup> Discriminators.

#### **Features**

- Does not require rewiring of card racks to accept four-channel Opticom phase selectors
- Allows quick system upgrades to four-channel Opticom phase selectors
- Is easy to install

## **Physical Dimensions**

**Length:** 4.0 in. (10.2 cm) **Width:** 0.5 in. (1.3 cm) **Height:** 4.5 in. (11.5 cm) **Weight:** 1.0 lbs. (30 g)

#### **Important Notice to Purchaser:**

EXCEPT FOR THE LIMITED WARRANTIES SET FORTH IN THIS DOCUMENT, GLOBAL TRAFFIC TECHNOLOGIES (GTT) MAKES NO OTHER WARRANTIES AND EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE.

GTT will, at its sole option, repair, replace or refund any amounts paid for any Opticom<sup>TM</sup> Infrared System component found to be defective in materials or manufacture within five (5) years from the date of shipment from GTT. See "Warranty and Extended Coverage" for details and limitations of the coverage plan. GTT will provide a functioning replacement component at a standard charge per unit for an additional five (5) years.

GTT warrants future system operability coverage as described herein. The warranties set forth in this document shall not apply to (A) incandescent lamps (confirmation lights) or (B) any Opticom infrared system components which have been (1) repaired or modified by persons not authorized by GTT; (2) subjected to incorrect installation, misuse, neglect or accident; (3) damaged by extreme atmospheric or weather-related conditions; or (4) subjected to events or use outside the normal or anticipated course.

IN NO EVENT SHALL GTT BE LIABLE FOR ANY INJURY (INCLUDING, WITHOUT LIMITATION, PERSONAL INJURY), DEATH, LOSS, OR DAMAGE (INCLUDING, WITHOUT LIMITATION, PROPERTY DAMAGE), WHETHER DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL OR OTHERWISE, ARISING OUT OF THE USE OR INABILITY TO USE, REPAIR OR FAILURE TO REPAIR, ANY GTT PRODUCT, REGARDLESS OF THE LEGAL THEORY ASSERTED. THE REMEDIES SET FORTH IN THIS DOCUMENT ARE EXCLUSIVE.

Sale and use of the Opticom infrared system is expressly restricted to authorized agencies of government customers, within their specific jurisdictions. However, because the infrared signal generated by the Opticom infrared system is not exclusive, GTT does not warrant exclusive activation by purchaser. Authorized users who desire to use or coordinate use of the Opticom infrared system with that of other jurisdictions must first obtain the prior written approval of each authorized user in the jurisdiction where use is sought.



Global Traffic Technologies, LLC 7800 Third Street North St. Paul, Minnesota 55128-5441 1-800-258-4610 651-789-7333 www.gtt.com

Global Traffic Technologies Canada, Inc. 157 Adelaide Street West Suite 448 Toronto, ON M5H 4E7 Canada 1-800-258-4610 Opticom is a trademark of Global Traffic Technologies, LLC.
Used under license in Canada.
Please recycle. Printed in U.S.A.
© Global Traffic Technologies, LLC 2007
All rights reserved.
75-0500-2248-4 (A)