



SPECIFICATIONS

INPUT CONNECTIONS: 115VAC, Walk, Don't Walk, Common, Protective Ground, from wiring inside a pedestrian sign (Ped Head).

OUTPUT CONNECTIONS: Approximately 20 Volts DC, Positive and Negative Power, Walk and Don't Walk, to a 4 Wire Push Button Station. The PCHU4W is provided with 2 mounting brackets and hardware which allow easy mounting inside all common types of pedestrian signs. It uses two ¼ amp 5x20mm fuses. It has built in surge protection and is epoxy coated for moisture protection. There are no settings or adjustments.

INFORMATION ON THIS DOCUMENT IS PROPRIETARY TO POLARA AND SHALL NOT BE USED, COPIED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT WRITTEN CONSENT OF POLARA.

Revised - 01/06/04										
REV.	DATE	LTR	E.C.O. NO.	BY	CKR	ENG	DSN	MFG	QA	FNL

4115 W. ARTESIA AVE. FULLERTON, CA. 92833					
TOLERANCES: .XXX ±.005 .XX ±.02 (EXCEPT AS NOTED)				SCALE	NONE
DRAWN BY	CKR.	ENG. MGR.	MFG. MGR.	SHEET 1 OF 1	
DATE	DSN. ENG.	Q.A. APP.	FINAL APP.	USE	
09-08-03				4W NAV	
TITLE				DWG. NO.	
4 WIRE POWER UNIT				PHCU4W	